

FERRAZ SHAWMUT DRIVE FUSE SELECTION TABLE

Eaton Cutler-Hammer 575V 3 phase SVX9000 Open Chassis Drive

525-690V Open Chassis Drive (Max Input Voltage 600V)				
Drive Catalog Number	Drive Application	HP	Max. Input Current, I_1 (A)	Main Fuse Part #
SPX200AO-5A4N1	Continuous Torque	200	208	HSJ350
	Variable Torque	250	261	HSJ450
SPX250AO-5A4N1	Continuous Torque	250	261	HSJ450
	Variable Torque	300	325	HSJ500
SPX300AO-5A4N1	Continuous Torque	300	325	HSJ500
	Variable Torque	350	385	HSJ600

Ferraz Shawmut HSJ fuses are intended to provide both branch circuit and drive protection. Fuse selection must be in accordance with drive manufacturers recommendations and conform to applicable national and local electrical codes. Recommended fuse ratings were selected for the maximum HP specified for the drive by the manufacturer, based on the most currently available information at the time. Fuses shown will minimize the amount of energy passed by the fuse under short circuit conditions, however, in some cases, component damage may result. Recommended HSJ fuse sizes are for non-bypass mode applications only.

Ferraz Shawmut 374 Merrimac St. Newburyport, MA 01950-1998
Phone: 978-462-6662 Fax: 978-462-0181
Cust. Serv. Fax: 800-535-8114 Tech. Serv. Fax: 800-535-8103
www.ferrazshawmut.com/OEM



March 2006